

Solenoid diaphragm pumps



The new 2 series

intelligent, precise, compact, good value...

sera - Solenoid diaphragm pump

of serie 204.1 are electronically controlled dosing pumps which can be used for many applications. They are designed for industrial use and guarantee highest operational reliability. Performance range between 1,2 l/h and 35 l/h, pressures up to max. 10 bar.

Application

Designed for the exact dosing of liquid media in all industrial fields. The dosing control is performed process-bound for the most part.

...further features of performance

- directly controllable
- high dosing accuracy
- long service life of diaphragms*
- high-quality materials
- linear control characteristic
- low maintenance
- low operating expenses
- leakage-free
- unlimitedly safe to run dry
- easy to operate
- low weight

* compared to common conventional diaphragms



Solenoid diaphragm pumps

Functions of the control electronics



R 204.1



C 204.1

Function	R 204.1	C 204.1
Manual operation	●	●
Manual stroke frequency adjustment	●	●
Profibus® DP - Interface ¹⁾		●
External START		●
External STOP	●	●
Pulse operation	●	●
Fractionation		●
Cycle delay		●
Analogue operation 0 – 20 mA		●
Analogue operation 4 – 20 mA	●	●
Analogue operation standardization		●
Charge manual		●
External charge START		●
Charge with timer		●
3 LEDs for status indication	●	●
Multiline illuminated text display		●
Operating messages in plain text		●
Fault indication in plain text		●
Menu - driven parameterization		●
Flow indication		●
Calibration		●
Working hour meter		●
Password protection		●
4 – key operation		●
2 – key operation	●	
2 digital outputs (PLC)		●
1 digital input (PLC or contact signal)		●
2 digital inputs (PLC or contact signal)	●	
1 analogue input (0/4 – 20 mA)	●	
2 analogue / digital inputs (optionally reversible)		●
Programmable input/output functions		●
Connection / evaluation 2-stage level monitoring	●	●
Connection / evaluation diaphragm rupture monitoring		●
Connection / evaluation flow monitoring		●
Connection / evaluation flow metering		●

¹⁾ available from July 2007

Solenoid diaphragm pumps



Technical data

Serie 204.1

Pump type	Nominal capacity		max. counter-pressure	max. suction height ¹⁾	Inlet-/Outlet-size	Driving power (solenoid)	Nominal stroke frequency
	Q _N 50/60 Hz [l/h]	Q _{stroke} [ml/Stroke]	p ₂ max. [bar]	[mWC]	DN [mm]	P _M [W]	n _N 50/60 Hz [min ⁻¹]
R../C 204.1 – 1,2e	0 – 1,2	0,13	10	3	5	20	150
R../C 204.1 – 2,4e	0 – 2,4	0,22	10	3	5	26	150
R../C 204.1 – 6,0e	0 – 6,0	0,66	6	3	5	26	150
R../C 204.1 – 7,0e	0 – 7,0	0,77	10	3	5	33	150
R../C 204.1 – 10e	0 – 10	1,1	6	3	5	33	150
R../C 204.1 – 14e	0 – 14	1,5	3	3	5	26	150
R../C 204.1 – 25e	0 – 25	2,7	3	3	10	33	150
R../C 204.1 – 30e	0 – 30	3,3	2,5	3	10	33	150
R../C 204.1 – 35e	0 – 35	3,8	1,5	3	10	33	150

¹⁾ with filled suction line

Electrical data

● Operating voltage:	100 – 240 V (50/60 Hz)	● Noise level (Noise level measurement DIN 45635-01-KL3):	58 +/- 5 dB (A)
● Inlet voltage control input:	5...30 V DC	● Weight:	3-5 kg
● Middle power draw with 150 strokes/min:	30 W	● Permitted ambient temperature:	+2°C to +40°C
● Current consumption during stroke (230 V):	max. 1,5 A	● Permitted humidity:	approx. 90%
● Minimale contact signal time:	50 ms		
● Analogue input resistance:	100 Ω		
● Digital Output:	PNP, 15...30 V DC, 250 mA		
● Pump protection type:	IP 65		
● Insulation class:	F		

Solenoid diaphragm pumps



Materials

The high quality of the materials ensures continuous and reliable operation. We have the optimum material* for each requirement.

Pump body and Valves:

PP-FRP, PVDF-FRP, PVC, 1.4571

Valve balls:

Glass, PTFE, 1.4401

Valve seals:

EPDM, FPM, FEP-covered

Working diaphragm:

PTFE-faced

Manual vent valve:

(only with pumps in FRP-execution)

PP-FRP, PVDF-FRP

Drive

The drive unit consists of a strong stroke solenoid in a robust housing made of plastic.

The rotation-safe stroke solenoid is equipped with a thermal overload protection.

Accessories

- Control cable for input signals
- Control cable for output signals
- Diaphragm rupture monitoring
- Flow controller
- Flow meter
- Automatic vent valve

For the optimum installation of a dosing pump we can supply all the necessary accessories such as valves, pulsation dampers, injection fittings, dosing tanks, etc. against your order.

* please ask us for any material required but not mentioned here



sera

Dosing
Feeding
Compressing

**Seybert & Rahier
GmbH + Co. Betriebs - KG**

sera-Straße 1 · D-34376 Immenhausen
Tel. + 49 56 73 99 90
Fax. + 49 56 73 99 91 55
e-mail: info@sera-web.de
Internet: www.sera-web.de

Local **sera** – Representative:

